


SLP-275 V/2

pluggable module, visual fault signalling, module locking

- two-pole varistor surge arrester
- installation to LV installations, especially to sub-distribution boards in TN-S systems
- for protection of the installations and equipments against impact of induced overvoltages during a lightning strike or switching overvoltages



Technical parameters

Parameter name	Parameter value
Type of SPD	T2
Mounting	DIN rail 35 mm
Nominal voltage	U _n 230 V AC
Maximum operating voltage	U _c 275.00 V AC
Maximum operating voltage	U _c 350.00 V DC
Type of network	TN
Maximum overcurrent protection	160 A gL/gG
Short-circuit current rating	I _{SCCR} 50.0 kA
Nominal discharge current (8/20 µs)	I _n 20.00 kA
Maximum discharge current (8/20 µs)	I _{max} 40.00 kA
Voltage protection level	U _p 1.35 kV
Voltage protection level at 5 kA	U _p 0.90 kV
Response time	t _a 25 ns
TOV 5 s L-N	335 V

TOV characteristic (TOV 5 s)	withstand
TOV 120 min L-N	440 V
TOV characteristic (120 min)	safe failure
Cross-section of connected conductors solid (min)	1.00 mm ²
Cross-section of connected conductors solid (max)	35.00 mm ²
Cross-section of connected conductors stranded (min)	1.00 mm ²
Cross-section of connected conductors stranded (max)	25.00 mm ²
Fault indication	red indication field
Degree of protection	IP 20
Range of ambient temperatures (min/max)	-40 / 80 °C
Humidity	5 - 95 %
According to standard	EN 61643-11:2012, IEC 61643-11:2011
ETIM Class	EC000941
Plug module	SLP-275 V/0
Customs tariff number	85363030
EAN	8595090516194